Date of compilation: 13/06/2022 Version: 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 67584 - Aquakote Koi-Kote (Clear) Part B

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Coating for concrete. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Aquakote Systems Ltd

Riverside House, River Lawn Road

TN9 1EP Tonbridge - Kent - United Kingdom

Phone: +44 (0) 1892 871 638 info@aquakotesystems.com www.aquakotesystems.com

1.4 Emergency telephone number: Call NHS 111 or a doctor if you feel unwell

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

GB CLP Regulation:

Classification of this product has been carried out in accordance with GB CLP Regulation.

Acute Tox. 4: Acute toxicity, Category 4, H302+H312+H332

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Dam. 1: Serious eye damage, Category 1, H318 Repr. 1B: Reproductive toxicity, Category 1B, H360F Skin Corr. 1: Skin corrosion, Category 1, H314 Skin Sens. 1B: Sensitisation, skin, Category 1B, H317

2.2 Label elements:

GB CLP Regulation:

Danger







Hazard statements:

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Repr. 1B: H360F - May damage fertility.

Skin Corr. 1: H314 - Causes severe skin burns and eye damage.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

Precautionary statements:

P280: Wear protective gloves/eye protection.

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.

Supplementary information:

EUH071: Corrosive to the respiratory tract.

Substances that contribute to the classification

benzyl alcohol; m-phenylenebis(methylamine); Formaldehyde, oligomeric reaction products with 4,4´-isopropylidenediphenol and m-phenylenebis (methylamine); Bisphenol A

2.3 Other hazards:

Date of compilation: 13/06/2022 Version: 1

SECTION 2: HAZARDS IDENTIFICATION (continued)

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Amines

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification	Chemical name/Classification	Concentration
CAS:	100-51-6	benzyl alcohol Acute Tox. 4: H302+H332 - Warning	30 - <50 %
CAS:	1477-55-0	m-phenylenebis(methylamine) Acute Tox. 4: H302+H332; Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1B: H317; EUH071 - Danger	30 - <50 %
CAS:	161278-17-7	Formaldehyde, oligomeric reaction products with 4,4´-isopropylidenediphenol and m-phenylenebis (methylamine) Acute Tox. 4: H302+H312; Aquatic Chronic 4: H413; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	10 - <30 %
CAS:	80-05-7	Bisphenol A Eye Dam. 1: H318; Repr. 1B: H360F; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	6 - <10 %
CAS:	621-56-7	3-(diethylamino)propane-1,2-diol Eye Irrit. 2: H319; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	3 - <6 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply,etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

Date of compilation: 13/06/2022 Version: 1

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and destroy using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Date of compilation: 13/06/2022 Version: 1

SECTION 7: HANDLING AND STORAGE (continued)

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits	
Bisphenol A	WEL (8h)	2 mg/m³
CAS: 80-05-7	WEL (15 min)	

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
benzyl alcohol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-51-6	Dermal	40 mg/kg	Non-applicable	8 mg/kg	Non-applicable
EC: 202-859-9	Inhalation	110 mg/m ³	Non-applicable	22 mg/m ³	Non-applicable
m-phenylenebis(methylamine)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1477-55-0	Dermal	Non-applicable	Non-applicable	0.33 mg/kg	Non-applicable
EC: 216-032-5	Inhalation	Non-applicable	Non-applicable	1.2 mg/m ³	0.2 mg/m ³
Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and m-phenylenebis (methylamine)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 161278-17-7	Dermal	1 mg/kg	Non-applicable	1 mg/kg	Non-applicable
EC: 500-607-5	Inhalation	3.52 mg/m ³	Non-applicable	3.52 mg/m ³	Non-applicable
Bisphenol A	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 80-05-7	Dermal	0.031 mg/kg	Non-applicable	0.031 mg/kg	Non-applicable
EC: 201-245-8	Inhalation	2 mg/m³	2 mg/m³	2 mg/m³	2 mg/m³

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
benzyl alcohol	Oral	20 mg/kg	Non-applicable	4 mg/kg	Non-applicable
CAS: 100-51-6	Dermal	20 mg/kg	Non-applicable	4 mg/kg	Non-applicable
EC: 202-859-9	Inhalation	27 mg/m ³	Non-applicable	5.4 mg/m ³	Non-applicable
Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and m-phenylenebis (methylamine)	Oral	0.5 mg/kg	Non-applicable	0.5 mg/kg	Non-applicable
CAS: 161278-17-7	Dermal	0.5 mg/kg	Non-applicable	0.5 mg/kg	Non-applicable
EC: 500-607-5	Inhalation	1.76 mg/m ³	Non-applicable	1.76 mg/m ³	Non-applicable

Date of compilation: 13/06/2022 Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Bisphenol A	Oral	0.004 mg/kg	Non-applicable	0.004 mg/kg	Non-applicable
CAS: 80-05-7	Dermal	0.002 mg/kg	Non-applicable	0.002 mg/kg	Non-applicable
EC: 201-245-8	Inhalation	1 mg/m³	1 mg/m³	1 mg/m³	1 mg/m³

PNEC:

Identification				
benzyl alcohol	STP	39 mg/L	Fresh water	1 mg/L
CAS: 100-51-6	Soil	0.456 mg/kg	Marine water	0.1 mg/L
EC: 202-859-9	Intermittent	2.3 mg/L	Sediment (Fresh water)	5.27 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.527 mg/kg
m-phenylenebis(methylamine)	STP	10 mg/L	Fresh water	0.094 mg/L
CAS: 1477-55-0	Soil	2.44 mg/kg	Marine water	0.009 mg/L
EC: 216-032-5	Intermittent	0.152 mg/L	Sediment (Fresh water)	12.4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	1.24 mg/kg
Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and m-phenylenebis (methylamine)	STP	69 mg/L	Fresh water	0.029 mg/L
CAS: 161278-17-7	Soil	81 mg/kg	Marine water	0.0029 mg/L
EC: 500-607-5	Intermittent	Non-applicable	Sediment (Fresh water)	490 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	49 mg/kg
Bisphenol A	STP	320 mg/L	Fresh water	0.018 mg/L
CAS: 80-05-7	Soil	3.7 mg/kg	Marine water	0.018 mg/L
EC: 201-245-8	Intermittent	0.011 mg/L	Sediment (Fresh water)	1.2 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.24 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding << UKCA marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

The Breakthrough Time indicated by the manufacturer must exceed	5
NON-disposable chemical protective gloves Mandatory hand protection NON-disposable chemical protective gloves The Breakthrough Time indicated by the manufacturer must exceed during which the product is being used. Do not use protective crear product has come into contact with skin.	not use protective creams after the

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

Date of compilation: 13/06/2022 Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

E.- Body protection

Pictogram	PPE	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	⊢	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Not available

Odour:

Not available

Not available

Nour available

Nour available

Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 192 °C Vapour pressure at 25 °C: 7 Pa

Vapour pressure at 50 °C: 55.81 Pa (0.06 kPa) Evaporation rate at 25 °C: Non-applicable *

Product description:

Density at 25 °C: Non-applicable *

Relative density at 25 °C: 1.074

Dynamic viscosity at 25 °C:

Kinematic viscosity at 25 °C:

Kinematic viscosity at 40 °C:

Concentration:

Non-applicable *

Non-applicable *

Non-applicable *

pH: 12

Vapour density at 25 °C:

Partition coefficient n-octanol/water 25 °C:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Date of compilation: 13/06/2022 Version: 1

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: 105 °C

Flammability (solid, gas): Non-applicable *

436 °C Autoignition temperature:

Lower flammability limit: Non-applicable * Upper flammability limit: Non-applicable *

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Non-applicable * Oxidising properties: Non-applicable * Corrosive to metals: Non-applicable * Non-applicable * Heat of combustion: Aerosols-total percentage (by mass) of flammable Non-applicable *

components:

Other safety characteristics:

Surface tension at 25 °C: Non-applicable * Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Not applicable

10.6 Hazardous decomposition products:

Contains substances which require external energy for spontaneous decomposition. Form explosive peroxides when distilled, evaporated or otherwise concentrated.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Date of compilation: 13/06/2022 Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
 - Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.
- B- Inhalation (acute effect):
 - Acute toxicity: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
 - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: May impair fertility
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
benzyl alcohol	LD50 oral	500 mg/kg	Rat
CAS: 100-51-6	LD50 dermal	2500 mg/kg	
	LC50 inhalation	11 mg/L (ATEi)	
Formaldehyde, oligomeric reaction products with 4,4 ´-isopropylidenediphenol and m- phenylenebis (methylamine)	LD50 oral	500 mg/kg (ATEi)	
CAS: 161278-17-7	LD50 dermal	1100 mg/kg (ATEi)	
	LC50 inhalation	Non-applicable	
Bisphenol A	LD50 oral	5100 mg/kg	Rat
CAS: 80-05-7	LD50 dermal	3000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	_

Date of compilation: 13/06/2022 Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acut	Genus	
m-phenylenebis(methylamine)	LD50 oral	1090 mg/kg	Rat
CAS: 1477-55-0	LD50 dermal	Non-applicable	
	LC50 inhalation	11 mg/L (ATEi)	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
benzyl alcohol	LC50	646 mg/L (48 h)	Leuciscus idus	Fish
CAS: 100-51-6		400 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	79 mg/L (3 h)	Scenedesmus subspicatus	Algae
m-phenylenebis(methylamine)	LC50	88 mg/L (96 h)	Oryzias latipes	Fish
CAS: 1477-55-0		15 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	20 mg/L (72 h)	Selenastrum capricornutum	Algae
Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and m-phenylenebis (methylamine) CAS: 161278-17-7		Non-applicable		
		110 mg/L (48 h)	Daphnia magna	Crustacean
		54 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Bisphenol A	LC50	4.6 mg/L (96 h)	Pimephales promelas	Fish
CAS: 80-05-7	EC50	3.8 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		

Chronic toxicity:

Identification	Concentration		Species	Genus
benzyl alcohol	NOEC 48.897 mg/L		N/A	Fish
CAS: 100-51-6	NOEC 51 mg/L		Daphnia magna	Crustacean
m-phenylenebis(methylamine)	NOEC	Non-applicable		
CAS: 1477-55-0	NOEC	4.7 mg/L	Daphnia magna	Crustacean
Bisphenol A	NOEC	0.16 mg/L	Pimephales promelas	Fish
CAS: 80-05-7	NOEC	3.16 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Date of compilation: 13/06/2022 Version: 1

SECTION 12: ECOLOGICAL INFORMATION (co	ontinued)
--	-----------

Identification	Degradability		Biodegradability	
benzyl alcohol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-51-6	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	94 %
m-phenylenebis(methylamine)	BOD5	Non-applicable	Concentration	14 mg/L
CAS: 1477-55-0	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	49 %
Formaldehyde, oligomeric reaction products with 4,4'- isopropylidenediphenol and m-phenylenebis (methylamine)	BOD5	Non-applicable	Concentration	20 mg/L
CAS: 161278-17-7	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	6 %
Bisphenol A	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 80-05-7	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %

12.3 Bioaccumulative potential:

Identification		Bioaccumulation potential		
benzyl alcohol		BCF	0.3	
CAS: 100-51-6			1.1	
P		Potential	Low	
m-phenylenebis(methylamine)		BCF	3	
CAS: 1477-55-0		Pow Log	0.18	
		Potential	Low	
Bisphenol A		BCF	67	
CAS: 80-05-7		Pow Log	3.32	
		Potential	Moderate	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
benzyl alcohol	Koc	Non-applicable	Henry	Non-applicable
CAS: 100-51-6	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3.679E-2 N/m (25 °C)	Moist soil	Non-applicable
m-phenylenebis(methylamine)	Koc	1300	Henry	Non-applicable
CAS: 1477-55-0	Conclusion	Low	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
Bisphenol A	Koc	796	Henry	1.013E-6 Pa·m ³ /mol
CAS: 80-05-7	Conclusion	Low	Dry soil	No
	Surface tension	3.76E-3 N/m (364.43 °C)	Moist soil	No

Date of compilation: 13/06/2022 Version: 1

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste:

HP8 Corrosive, HP14 Ecotoxic, HP6 Acute Toxicity, HP10 Toxic for reproduction, HP13 Sensitising

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



14.1 UN number: UN2735

14.2 UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis

(methylamine))

14.3 Transport hazard class(es): 8

Labels: 8
14.4 Packing group: II
14.5 Environmental hazards: No

14.6 Special precautions for user

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Transport in bulk according N

to Annex II of Marpol and

the IBC Code:

Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:

Date of compilation: 13/06/2022 Version: 1

SECTION 14: TRANSPORT INFORMATION (continued)

14.1 UN number: UN2735

14.2 UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis

(methylamine))

14.3 Transport hazard class(es):

Labels: 8

14.4 Packing group: Π 14.5 Marine pollutant: Nο

14.6 Special precautions for user

Special regulations: 274 FmS Codes: F-A, S-B Physico-Chemical properties: see section 9 1 I

Limited quantities: Segregation group: SGG18

14.7 Transport in bulk according Non-applicable

to Annex II of Marpol and the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



14.1 UN number: UN2735

14.2 UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis

(methylamine))

14.3 Transport hazard class(es): Labels: 8

14.4 Packing group: ΙΙ 14.5 Environmental hazards: No

14.6 Special precautions for user

Physico-Chemical properties: see section 9 14.7 Transport in bulk according Non-applicable

to Annex II of Marpol and

the IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

Substances listed in UK candidate list of substances of very high concern (SVHCs): Bisphenol A

The Control of Major Accident Hazards Regulations 2015:

Non-applicable

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Product classified hazardous under the CMR. Sale and distribution to the general public is prohibited. Due to its CMR category, it is essential to apply the specific measures for workplace hazard prevention covered in articles 4 and 5 of the 2004/37/EC Directive and later modifications.

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- —tricks and jokes.
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Bisphenol A. Shall not be placed on the market in thermal paper in a concentration equal to or greater than 0,02 % by weight after 2 January 2020.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

Date of compilation: 13/06/2022 Version: 1

SECTION 15: REGULATORY INFORMATION (continued)

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H412: Harmful to aquatic life with long lasting effects.

H317: May cause an allergic skin reaction.

H360F: May damage fertility.

H302+H312+H332: Harmful if swallowed, in contact with skin or if inhaled.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation:

Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin.

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Aquatic Chronic 4: H413 - May cause long lasting harmful effects to aquatic life.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Repr. 1B: H360F - May damage fertility.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

Skin Corr. 1: Calculation method Eye Dam. 1: Calculation method Aquatic Chronic 3: Calculation method Skin Sens. 1B: Calculation method Repr. 1B: Calculation method Acute Tox. 4: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

Safety data sheet According to UK REACH

67584 - Aquakote Koi-Kote (Clear) Part B

Date of compilation: 13/06/2022 Version: 1

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50

LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.